
Standards Compliance

SINOBOOM 1330SE



Dimension		Metric
Dimension Nov Working Height		5.8m
Max Working Height		
A Max Platform Height		3.8m
B Max Horizontal Extension		0.6m
C Length-Stowed		1.42m
D Width-Stowed		0.76m
	Rail Folded	1.67m
Height - stowed	E Rail Unfolded	1.97m
	Fixed Rail	1.97m
F Wheelbase		1.11m
Ground Clearance(Pothole Guard Stowed)		65mm
Ground Clearance(Pothole Guard Deployed)		20mm
Platform Dimensions(L×W×H)		1.34m×0.7m×1.1m
Performance		
Platform Allowable Occupants(Indoor)		2 persons
Platform capacity		240kg
Lift Extension Capacity		100kg
Drive Speed-Stowed		4km/h
Drive Speed-Raised		0.8km/h
Lift Time(Unloaded)		30s~33s
Descent Time(Unloaded)		25s~30s
Gradeability		25%
Turning Radius(Inside/Outside)		0.3m/1.35m
Tilt Rating(Front to Back/Side to Side)		3°/1.5°
Tyres-solid		230×80mm
Power		
Batteries		12V×2/115Ah
Power Source		24V DC
Drive Mode		Motor, Rear wheel
Charger Input		100~240V AC
Charger Output		15A
Hydraulic System Capacity		5L
Weight		
Weight(Indoor)		880kg
Standards Compliance		ISU/CE/VNSI/CSV/VS/CITED



ISO/CE/ANSI/CSA/AS/CU-TR